(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 22 September 2005 (22.09.2005)

PCT

(10) International Publication Number $WO\ 2005/087671\ A1$

(51) International Patent Classification⁷: C03B 17/00

(21) International Application Number:

PCT/US2005/007532

(22) International Filing Date: 4 March 2005 (04.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:


60/550,464 4 March 2004 (04.03.2004) US

- (71) Applicant (for all designated States except US): QUANTUM QUARTZ, LLC [US/US]; 84 Weldon Parkway, Maryland Heights, MO 63043 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MORRILL, Vaughan, Jr. [US/US]; 11949 Charter House Lane, Creve Coeur, MO 63146 (US). WILKE, Roger, Jr. [US/US]; 346 Country Meadows Drive, St. Charles, MO 63303 (US).

- (74) Agent: POLSTER, J., Philip; Polster Lieder Woodruff & Lucchesi, 12412 Powerscourt Drive, Suite 200, St. Louis, MO 63131 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND DEVICE FOR CONTINUOUSLY FORMING OPTICAL FIBER CONNECTOR GLASS AND OTHER CLOSE TOLERANCE COMPONENTS



(57) Abstract: A method and device for making high precision glass forms (110). A glass rod (1) is pushed into a melting tube (47) and the glass form is pulled from the chamber. Preferably, both the push rate and the pull rate are controlled. Fiber optic glass ferrules and other components manufactured by the use of this invention have precision dimensions that fall well within the tight dimensional tolerances required for ferrules and others.

WO 2005/087671 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.